

T-40

METAPACE T-40

Powerful POS and Hospitality
Printer with Triple Interface

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 250mm/sec.
Print width	max. 80/57.5 +/- 0.5 mm
Resolution	203 x 203 dpi
Character size	Font A: 12x24, Font B: 9x27, Kanji Font A: 24x24
Sensors	Paper end, black mark, near paper end, cover open, head temperature

MEDIA

Media type	Thermal paper
Paper supply	Paper roll
Width	57.5/80/82.5 mm
Roll diameter	max. 82.5 mm
Media strength	0.06–0.10 mm

ELECTRONICS

Memory	RAM: 2 MB, Flash: 4 MB
Interfaces	Triple interface USB, serial, Ethernet, cash drawer, WLAN (optional), Bluetooth (optional)
Power supply	AC 120V~230V ± 10%, DC 24V, 2.5A (included)
Barcodes	UPC-A, UPC-E, CODE 39, CODE 93, CODE 128, EAN 8, EAN 13, ITF, Codabar, PDF417, QR, Maxicode
Emulation	ESC / POS
Reliability	150 km TPH, 2,000,000 cuts, 70,000,000 lines

SOFTWARE

Drivers	Windows, Linux, OPOS, JPOS
Emulation	ESC / POS
SDK	Android, iOS

SPECIFICATIONS

Standard	USB cable, RS232 cable, power adapter + power cable, cable protection, QSG, drivers + tools, test receipt roll
----------	--

WARRANTY

Period	3 years
--------	---------

HOUSING

Dimensions (WxHxD)	127 x 127 x 134 mm
Colour	Black

CONDITIONS

Temperature	Operating: 5 °C–45 °C Storage: -40 °C– +60 °C
Humidity	Operating: 20 %–90 % RH Storage: 10 %–90 % RH

Highlights

- + Greyscale printing at up to 250mm/sec. print speed
- + Fits everywhere: compact yet appealing design
- + Everything in one box: unpack and get started
- + Service life of the print head: 150 km
- + Choice of top or front output

